



DLP™ projector  
J5P Pico

		J5P Pico			
Reference Model		DP-2510	DP-3510	DP-6610	DP-7610
Projection System		Texas Instruments DLP™ Technology			
Panel		0.55" x 1, Type X	0.55" x 1, Type X	0.62" 720p, Type A	0.65" WXGA, Type A
Data Processor		2xLVDS DLP™ with DDP2230			
Resolution	Native	SVGA 800x600	XGA 1024X768	1280X720P	WXGA 1280x768
	DDP2230 Compatibility	Up to UXGA 1600x1200@60 Hz	Up to UXGA 1600x1200@60 Hz	Up to WXGA+ 1680x1050@60 Hz	Up to WXGA+ 1680x1050@60 Hz
Brightness (Typical)	Standard mode (200W)	1900 ~ 2000 ANSI Lumens	1900 ~ 2000 ANSI Lumens	1800 ~ 1900 ANSI Lumens	1900 ~ 2000 ANSI Lumens
	Eco mode (160W)	1400 ~ 1500 ANSI Lumens	1400 ~ 1500 ANSI Lumens	1400 ~ 1500 ANSI Lumens	1400 ~ 1500 ANSI Lumens
Contrast Ratio		1800:1	1800:1	1800:1	1800:1
Brightness Uniformity (Typical)		80%	80%	80%	80%
Projection Lens		Manual Zoom, Manual Focus			
Digital Zoom		YES			
Zoom Ratio		1.15:1			
Focal Length		21.3 ~ 24.5mm; 2m@52"		21.3 ~ 24.5mm; 2m@59"	21.3 ~ 24.5mm; 2m@60"
Projection Distance		1.5m ~ 10m (overdrive to 11.5m)			
Projection Screen Size		34" ~ 260" (overdrive to 300")		38.5" ~ 300"	39" ~ 295"
Throw Ratio (D/W)		1.9 ~ 2.2	1.9 ~ 2.2	1.5~1.8	1.5~1.8
Optical Offset		128%	128%	136%	128%
Aspect Ratio		4:3 & 16:9			
Keystone Correction	Vertical	+/- 15°			
Frequency	H-Sync	15, 21.87~91.4 KHz			
	V-Sync	43 ~ 87Hz			
Data Compatibility		VGA, SVGA, XGA, SXGA, Macintosh			
Video Compatibility		NTSC/NTSC 4.43, PAL B/G/H/I/M/N 60, SECAM, 480i/480p/720p/1080i			
Lamp Mode (Standard/Eco)		200W/160W			
Lamp Life (Standard/Eco)		TBD			
Acoustic Noise (Standard/Eco)		Typical: 40 / 37 dB			
Power Supply		AC input 110~240 Voltage (auto ranging)			
Power Consumption (Standard/Eco)		250W / 210W			
Dimensions (WxDxH)		220x178x71mm			
Weight (typical)		3.2lbs			
Safety & Regulatory Compliance		FCC-B, UL/Cul, TUV, CB, CE, CCC			
Led Indicator		Power, Lamp Standby, Over Temp			
Build-in Speaker		1W Mono Speaker			
IO Panel	Input Terminals	VGA x1, S-Video x1, Composite x1, Mini jack x1	VGA x1, S-Video x1, Composite x1, Mini jack x1	VGA x1, S-Video x1, Composite x1, HDMI x1, Mini jack x1	VGA x1, S-Video x1, Composite x1, Mini jack x1
	Output Terminals	NA			
	Control Terminals	USB (type B) x1			

1. All Features, specifications, model numbers are subject to change without notice.
2. Digital Light Processing and DLP are registered trademarks of Texas Instruments.



435A0612



#### TAIWAN

DELTA ELECTRONICS, INC.  
Display Business  
186, Ruey Kuang Road, Neihu, Taipei 11491,  
Taiwan, R. O. C.  
TEL: +886-2-8797-2088  
FAX: +886-2-8797-2120

#### CHINA

Delta Electronics (Jiang Su) Ltd.  
Visual Display Plant  
1688 Jiangxing East Road,  
Wujiang Economy Development Zone,  
Wujiang City, Jiang Su Province, People's  
Republic of China Post code: 215200  
TEL: +86-512-6340-3008  
FAX: +86-769-6340-7290

#### JAPAN

DELTA ELECTRONICS (JAPAN) INC.  
Delta Shibadaimon Building  
2-1-14 Shibadaimon,  
Minato-Ku, Tokyo, 105-0012,  
Japan  
TEL : +81-3-5733-1111  
FAX : +81-3-5733-1211

#### U.S.A.

Delta Products Corporation  
15125 SW Koll Parkway, Suite K,  
Beaverton, OR 97006, U.S.A.  
TEL : +1-503-533-8444  
FAX : +1-503-533-0204

#### EUROPE

DELTA ELECTRONICS (EUROPE), LTD.  
Wegalaan 16  
2132 JC Hoofddorp  
The Netherlands  
TEL: +31-23-566-8927  
FAX: +31-23-566-8910

